

Cale horizontale U ouvert

Pour calage d'armature horizontale sur chantier ou préfabriqué.

Longueur standard: 2,00 m



Référence	Dimension	Conditionnement		Poids en kg	
	Hauteur	Botte	Palette	Botte	Palette
1UFIX152000	15mm	100m	5400m	10,0	540
1UFIX202000	20mm	100m	5400m	12,5	675
1UFIX252000	25mm	100m	4200m	16,0	672
1UFIX302000	30mm	100m	3600m	18,0	648
1UFIX352000	35mm	60m	2400m	8,8	528
1UFIX402000	40mm	60m	2400m	10,0	600
1UFIX502000	50mm	60m	1680m	19,5	546
1UFIX602000	60mm	40m	1200m	16,4	492

Cale horizontale U fermé

Pour calage d'armature horizontale pour la pose sur isolant.

Longueur standard: 2,00 m



Référence	Dimension	Conditionnement		Poids en kg	
	Hauteur	Botte	Palette	Botte	Palette
1UFIX152000	10mm	100m	7000m	12,0	840
1UFIX202000	15mm	100m	5400m	16,0	702
1UFIX252000	20mm	100m	5400m	16,0	864
1UFIX302000	25mm	100m	4200m	18,0	756
1UFIX352000	30mm	100m	3600m	23,0	828
1UFIX402000	35mm	60m	2880m	15,7	754
1UFIX502000	40mm	60m	2100m	18,6	651
1UFIX602000	50mm	60m	1680m	30,0	840